



Grade 9	intact Details
Customer Name:	Ship to Customer Address:
Advisor:	Shipping Name:
Address:	Shipping Address:
Phone:	Phone:
Email:	Email:
Additional	Information
Notes:	Current Wheelchair:
	Customer Weight:
	Customer Height:
	Customer Disability:
Ot	her





Guide: Base product	Required option	Optional Extra	/! Critica	al Information	(i) Ir	nformation Needed	Non certified Sub4 weight
			PRODUCT S	TYLE			option
SBTXZ010	OCTANE SUB4 OCTANE SUB4						
XA070	Open design Open design						
XA080	Closed design (Non Certification Closed design	ed Sub4 option)					
Max User We	ight 110kg (242lbs)						
PLEASE NOTE: A	ALL RGK CHAIRS ARE HAND BUIL				TOLERANCE	OF +/- 5MM	
			CAD APPRO	OVAL			
XW010	ORDER CAD drawing for approve ORDER CAD drawing for approve	al	nents ONLY)	XW009	QUOTE ON	LY (NO CAD FOR APPRO LY (NO CAD FOR APPRO	
XW012	QUOTE / CAD drawing for appro	val	nents ONLY)	XW011		CAD FOR APPROVAL) CAD FOR APPROVAL)	
		KE	MEASURE	MENTS			
XY010	Seat width (Inside of sideguards	;)				X	Y010
<u></u>	mm	(Max - 440mm) (Min - 250mm)					
XY020	Seat length						
<u>^</u>	Seat length mm	(Max - 440mm) (Min - 250mm)					
□xy030	Extra seat length (Provides addin Extra seat length mm	ional leg support & (Max - 440mm tol					
XY050	Front frame height Front frame height mm	(Max - 520mm) (Min - 380mm)		\uparrow	X	XY020	
xy060	Rear frame height Rear frame height mm	(Max - 500mm) (Min - 360mm)		XY050			090AX
XY070	Frame length Frame length mm	(Max - 625mm) (Min = XY020 + XY	′030 + 140mm)	1	(072	XY070	
XY072	Castor position Castor position mm					XA020	
	Optimise measurements Optimise measurements				_ (
XA020	Ergonomic seat Ergonomic seat Specify length						
①	mm	(Standard = 120m	m)				





		FRONT FRAME A		EST	
Specify win (When cor XY091 , dir inbetween main bend	mm mbined with mension is the centre of the	Front Frame XY080 Footrest Design 0	Specify (When XY080, smalle)	Parallel taper design width mm combined with dimensions must be r by 20mm)	
<u> </u>	Max Height Achievable 110mm	Footrest Meas	Casto	Square design Square design r Wheel Max Height Achievable 4" 130mm	
XY115	Front footrest height	FOULIEST MEAS	urements	Ħ	
<u>^</u> !\	ront footrest height mm (any footrest over 160mm mc Rear footrest height Rear footrest height	(Min - 40mm, 60mm for front wheel attachment) we to highlevel footrest) Std = 20 lower than front heigh (Min - 40mm, 60mm for	ot XY	7115 XY125	XY120
(i) [mm (any footrest over 160mm mo	front wheel attachment) eve to highlevel footrest)	4000	V X1123	
1 [4 □ xB200	Footrest length Footrest length mm High level footrest (Non-certi High level footrest (Max Indicate front footrest height: mm	- 100mm)	avy duty upgrade		
		Footrest 5	Style		
	oular Titanium footrest Sub4 (: oular Titanium footrest Sub4	15.88mm x 1mm) (Height adjustable) (Height adjustable) Footrest ((A) ☐ XBC Cover	7 Tubular titanium (Non Certified Su Tubular titanium (
	ntweight carbon fibre cover	(With weight saving cut-out	t)	Footplate width Sub4 ce (Std if no option selected Footplate width Sub4 ce	(b
_	Cut-Out (Non Certified Sub4 Cut-Out	Poption)	4 	(Std if no option selected Footplate width Standar (Non Certified Sub4 opt	d) d (optimised plate width)





	CAS	TOR WHEELS, FO		HEEL L	OCKS		
XC135	Aluminium centre 4"x1.25" Aluminium centre 4"x1.25"	Choose colour below: Choose colour below:					
	Silver hub & black tyre (Std) Silver hub & black tyre (Std) Black hub & black tyre Black hub & black tyre Purple hub & black tyre Purple hub & black tyre	Green hub & b Green hub & b Red hub & blac Red hub & blac Blue hub & bla	lack tyre ck tyre ck tyre ck tyre ck tyre				
(4) □ SBTXC155	Forged carbon centre 4"x1.4" (Forged carbon centre 4"x1.4"	Non certified Sub4 option)	ı				
4 □XC140	Aluminium centre 5"x1.4" (Nor Aluminium centre 5"x1.4"	n certified Sub4 option)	(Silver hub a				
A □ XC145	Aluminium centre 6"x1.4" (No	n certified Sub4 option)	(Silver hub a				
		Castor	Forks				
	Performance castor fork (Std Performance castor fork (Std	Note: Colour follows acce		-	I castor fork I castor fork	contact per	ater distance between atch and steering axis utter at higher speeds. lows accent
	Castor pin width Castor pin width Optimise measurements (Minimum width for clear castor remaximum wheelbase length) Optimise measurements (Minimum width for clear castor remaximum wheelbase length)	otation and	XY330				
		Wheel Loc	k Options				
SBTXD036 XD020 XD050	Compact scissor with lightweig Compact scissor with lightweig Underseat scissor (Non certifie Underseat scissor Push to lock (Non certified Sub Push to lock	cht fixing		TXD085	(Only with fixe	Sub4 option cks (Indicate L/W fixing (Indicate centre of Indicate cent	n) c colour) Indicate colour) gravity)
XD010	Omit wheel locks Omit wheel locks	CIDEOL CIDEOL	Е	BLACK BLACK	(Only with fixe PURPLE PURPLE Black Std if no o	RED RED	gravity) BLUE BLUE
	Cidamand	SIDEGL	JAKDS	_	C'al a su a sal	outste Francis	
XE055	Sideguard Screw on lightweight carbon fil Screw on lightweight carbon fil		XE	065	Screw on light	•	on fibre w/fender
	Sideguard Measurements (vidual above tyre (Follow tyre - x. 25mm)					Aleasureme Standard) Standard)	înts
indi max Lev	widual above tyre (Follow tyre - x. 25mm) mm el with tyre (Follow tyre) el with tyre (Follow tyre)		ı	Individua	al above tyre 0mm) al above tyre	7	



SERIAL NO: _____



			ACKREST	
		Backrest I	Measurements	
XY230	Backrest height (Max) Backrest height (Max - 400mm) Specify height	(- 400mm)	XG010 (4)	Fixed Backrest (non-folding) Fixed Backrest (non-folding) Folding backrest with 2 position snap lock and angle
①	mm		The same of the sa	adjust (Non certified Sub4 option) Folding backrest with 2 position snap lock and angle adjust
		Ergono	mic Options	
XY360	Backrest angle Backrest angle 3 0 +3 +5	XY360	XG100	Ergonomic backrest Ergonomic backrest
		100	①	Vertical height Vertical height mm
Individual	De (Max -10/+20 Deg)	g	①	Rearward position Rearward position
XG110		of backrest posts) of backrest posts)	XG120	Outward flare (inside of backrest posts) Outward flare (inside of backrest nosts) X6120
①	Specify width or per side	mm XG110		Specify width or per side mm
			BER BAR	
XY390	Specify Camber Ar Camber angle Camber angle	gle	SBTXH100	Centre of Gravity Single post fixed centre of gravity
<u>^</u>			\wedge	Single post fixed centre of gravity (25-125mm)
			<u>✓ !</u>	Square back adjustable centre of gravity (25-125mm) (Non Certified Sub4 option)
			<u>^</u>	Square back adjustable centre of gravity (25-125mm) mm
			(4) ■SBTXH140	Round back adjustable centre of gravity (60-125mm) (Non Certified Sub4 option) Round back adjustable centre of gravity
		Comba	<u>^</u>	(60-125mm) mm
		Camber	Bar Options	
		graded Camber Bar to suit) graded Camber Bar to suit)		atec Bloc and Mount atec Bloc and Mount
4 □xG070	Screw in push handles Screw in push handles	(Non Certified Sub4 option)	(4) □xG080	Flip down push handles Flip down push handles
(4) □ x _J 100	Single sport anti tip Single sport anti tip	(Non Certified Sub4 option)		
l .				





	FRAME	E FINISH OPTIONS	S	
	Frame ar	nd Footrest (Choose One)	
SBTXN030 Bead Blast frame Bead Blast frame SBTXN050 Polished frame Polished frame		\odot	Powder coat frame (I	Non certified Sub4 option)
	Accen	t Colour (Choose One)		
Note: Accent colour includes, forks & co	Silve Silve Blue	er accent er accent e accent e accent		
		JPHOLSTERY Seat Upholstery		
XP045 Sub4 Seat sling strap at Sub4 Seat sling strap at	ljustable	XR050	Carbon fibre seat plate Carbon fibre seat plate	(Non certified Sub4 option)
	Ba	ackrest Upholstery		
XP035 Airtech Sub4 backrest : Airtech Sub4 backrest :		A □xp050	Airtech backrest strap adj (Non certified Sub4 opti Airtech backrest strap adj	on)
		(4) □ xp070	Backrest upgrade to leath (only with Airtech uphols (Non certified Sub4 opti- Backrest upgrade to leath (only with Airtech uphols	stery XP050) on) ner corners (Black)
		4 □ XP110	Backrest with zip pocket (only with Airtech uphols (Non certified Sub4 opti Backrest with zip pocket (only with Airtech uphols	on)
		(4) □ XP170	Individual backrest embro Please complete page 9 (only with Airtech uphols Individual backrest embro (only with Airtech uphols	stery XP050) pidery
	Backrest U	pholstery Stitching Option	ons	
Silver Silver	Black Black	Blue Blue		Individual: Individual:
Red Red	Orange Orange	Purple Purple RGK Logo Colour		
White (Std)	Black	Blue		Individual:
White (Std) Red Red	Black Orange Orange	Blue Purple Purple		Individual:



SERIAL NO: _____



	REAR		certified weight of Wheel Size	options)	
XY420	24" Wheels 24" Wheels	XY430	25" Wheels 25" Wheels Wheel Gap		
XY460	Rear wheel gap Rear wheel gap 15 20 25	7460 A A A A A A A A A A A A A A A A A A A	wileel G ap		
		Rear W	/heel Options		
XK075	Spinergy BLXL 18 blade spoke Spinergy BLXL 18 blade spoke	N/A IN SILVER HUB N/A IN SILVER HUB	—	.50 Spinergy CLX 18 carbon b N/A IN SILVER HUB Spinergy CLX 18 carbon b N/A IN SILVER HUB	·
XK226	Titanium 100mm quick release				
Spinergy Col	Titanium 100mm quick release our Options:	axle pins			
Black spoke Black spokes Red spokes Red spokes Purple spol Purple spol Spinergy And	white spokes Blue spokes Blue spokes Blue spokes Orange spokes	Yellow spokes Yellow spokes Pink spokes Pink spokes Green spokes Green spokes	XK180	Individual spoke design Individual spoke design Inside: Outside: Outside:	(Specify colour) (Specify colour)
(S	Black hub XK200 Std option) Black hub std option)	Silver hub (n/a with BLXL/CLX) Silver hub (n/a with BLXL/CLX)	Red hub/ri	BLXL only)	
XK202 P	Purple hub/rims XK203 LX, XLX & BLXL only) Purple hub/rims LX, XLX & BLXL only)	Blue hub/rims (LX, XLX & BLXL only) Blue hub/rims (LX, XLX & BLXL only)	XK204 Gold hub/i (LX, XLX & Gold hub/i	rims BLXL only)	
(1	LA, ALA & DEAL OHIY		Vithout Wheels	DEAL OILY)	
SBTXK040	Supply without Wheels and Axl Supply without Wheels and Axl	(.) .	neel Type:	Туге Туре:	
			osition / Options		
XY480	Narrow set handrim Narrow set handrim		XY485	Wide set handrim Wide set handrim	
XL090	Remove excess mounting tabs Remove excess mounting tabs	(recommended for some of the commended for s	small wheel gaps)		
XL010	Aluminium hard anodised 6 tab		drim Styles selected) XL040	Titanium 6 tah	
	Aluminium hard anodised 6 tab	(Std if no option		Titanium 6 tab Titanium 6 tab	
XL160	Elipse 6 tab (replacement for Elipse 6 tab (replacement for for for for for for for for	- ·	XL035	Natural Fit LT Natural Fit LT	
XL020	Tetra grip 6 tab Tetra grip 6 tab		XL150	Carbolife Gekko Carbolife Gekko	Black Silver
XL100	Para grip 6 tab		XL170	Carbolife Curve L (Black) Carbolife Curve L (Black)	Black Silver
		Tyr	e Options		
XM060	Schwalbe One (Lightest option) Schwalbe One (Lightest option)		XM130	Kenda black Kenda black	
XM010	Kenda Grey B	lue Red	XM050	Kenda K885 mountain bike t	
XM020	Schwalbe Marathon Plus Schwalbe Marathon Plus			Kenda K885 mountain bike t (24",25" only)	cyre (24",25" only)
XM040	Shox solid airless Shox solid airless				
- www.		Inner Tub	e Valve Options		
XY500	Schraeder inner tube valve (Standard if no option selected Schraeder inner tube valve (Standard if no option selected		XY490	Presta inner tube valve Presta inner tube valve	
		•	Accessories		
хк130	Spokeguard with design (pair) Spokeguard with design (pair)	fitted not fitted	XK145	Black Gloss Spokeguards Black Gloss Spokeguards	fitted not fitted





* Indicates options that are not part of the certified Sub4kg weight of the product





	Q	CUSHION (** no	n certified weight op nion foam options	otions)
XP080	Cushion foam	(select density and size below		
"	Cushion foam	(select density and size below		
	Soft (CM:		Medium (CMS050) Medium (CMS050)	
	50mm	E	75mm 75mm	100mm
	50	Cush	ion cover upgrades	255,,,,,,
XP085	Nylon cushion o	, ,		
XP090	Airlite cushion of	, ,		
XP100	Leather cushion	cover (Black)	ASE PROVIDE JAY ORDER FO	nRM
_		Jay Floudets - FLE	ASE PROVIDE JAT ORDER TO	AMA
JAY Cusi (Price de JAY Cusi	ependant on size /	option) Refer to Jay Order Fo	rm	
	ependant on size /	option)		
	ependant on size /	(option) Refer to Jay Order Fo	rm	
(Price de	ependant on size /	option)		
	tmyer Headrest ependant on size /	(option) Refer to Jay Order Fo	rm	
	tmyer Headrest ependant on size /	option)		
	A	FRAME OPTIONS (**	non certified weigh	t options)
XR060	Welded calf stra	ap mounting loops (To lo	ocate calf strap on front frame)	H
_	Welded calf stra	ap mounting loops (To lo	ocate calf strap on front frame)	H
	Specify height fr	rom floor		
	Optimise	measurements		
	Optimise (4)	measurements ACCESSORIES (** n	on certified weight	options)
		-		
XR080	Frontwheel asse		·	lue silver
XP120	Frame protecto	rs Neoprene zip fasten (Black)		
	Frame protector	rs Neoprene zip fasten (Black)		
XP420		rs Nylon velcro fasten (Black) rs Nylon velcro fasten (Black)		
XR010	Seat pouch velc	ro attach (Black)		
	Seat pouch velc	ro attach (Black)		
XR200	Rucksack with R			
VDOOO				
XR090	Tool kit Tool kit			
XS065	Sub4 Calf Strap Sub4 Calf Strap			
		options that, when chosen, w	ill not enable RGK to guarant	ee a Sub4kg product weight





INDIVIDUAL BACKREST EMBROIDER	Y
PLEASE PROVIDE JPEG IMAGE AT TIME OF ORDER AND NOTE P	OSITION BELOW
RCK	
767	
BRACE BAR	
C NOTES:	
OFF SPEC REQUEST* (please specify below the page number(s) and details	OFF SPEC REQUES
to which the off spec request applies.	APPROVED (for intern
	RGK office only)
	x
	RGK Internal Sign-off