

RETAIL



Life	RT

																					гие г
er to:												•	Invoi	ice to):						
e:											CE	L	Nam	ie:							
t:													Stree	et:							
:			Po	ostal co	de:						UK CF		Tow	n:							Postal code:
il:											-	E-Ma	ail:								
			Fa	ax:									Tel:								Fax:
r date:]			Mark	ked fo	or:						
nase or																					
per req	uired:														rder i						- Cost ontic
															andai o cost	a optio	n				= Cost optio
																opuo					
					-		17		Y							eight	:				125 kg
		Base Price				V							USE	RW	EIG	ΗT					kg
		£2,195					- 9						Manda	atory inf	formatio	on to en	sure co	orrect co	onfigura	ation	
												1801-1			-	7000	-				QPP01
	OF AT		CTION	CLIE											out cl	Isnio	1)				
	28	WIDTH SELE	32	1	1rea 1r 34	1	1151de 36		88	1	13ide ii 40	1	tube (0 12	r Ó	4	4	6	4	8	1	
	0	0	0		0		0		0		0		0		0		0)		
	Ŭ	-	Ū		•		- -		-		-		-		-				-]	
	SEAT	DEPTH SELE	CTION	- meas	ured	in cm	I								_						
	32* 34* 36 38				36 38 4				40 42					46 * not available with frame widths 34cm or g					s 34cm or greater		
	0	0	0		0		0	(0		0		0			* not a	availat	ole with	swing	j-away	frame
		ŝ	Short Fra	ame				М	ediur	n Fra	me	Lo	ng Fra	ame							
FRO	ONT SE	EAT HEIGHT	SELEC	TION: i	n dep	enda		of fron n t se a					versio	ons							
	Г	Fork	Type (m	ım)		36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	
		Hen	ni Versio	on			0	0	0												
		Carbotec	ture (11	1 mm)		0	0	0	0	0	0										
	4"	Aluminiu	m (123 n	nm) (1)			0	0	0	0	0	0									
		Aluminiu	m (143 m	nm) (1)					0	0	0	0	0	0							
		Aluminiu	m (168 m	nm) (1)								0	0	0	0	0	0				
			ni Versio				0	0	0	0											
stor		Carboted						0	0	0	0	0									
cas	5"	Aluminiu						0	0	0	0	0	0								
Front castor		Aluminiu							0	0	0	0	0	0	0						
F	\vdash		inium (168 mm) (1)					-			-		0	0	0	0	0	0			
		Hemi Version						0	0	0	0	0									
	~ "		Carbotecture (111 mm)								0	0	0								
	6"		Aluminium (123 mm) (1)								0	0	0	~	0	_					
		Aluminium (143 mm) (1) Aluminium (168 mm) (1)								0	0	0	0	0	0	0	~	<u>^</u>			
	7"		-								0	0	0	0	0	0	0	0	0		
		Aluminiui emi version on		, , ,									0	0	0	0	0	0	0	0	L
REA		AT HEIGHT S	ELECTI	ION: in	depe		ce of	rear v	wheel	l size											
	-	au	Rear s	-	ī —	1						1									
	Re	ar wheels 22"		37 38	39	40	41	42	43	44	45										
		22" 24"	0 (0	0	0		0	0												
		24		0	0		0	0	0	0	0	1									

The rear seat height can only be between 0 and 11cm below the selected front seat height.

(1) compatible with power add on devices

														£
	SE	AT UPHOLSTER	Y ANI	D CU	SHI	ONS								
Seat slings	5													
LRT020008	0	Seat sling, nylon, te	nsion-,	depth	adju	stable								
LRT020009	0	Seat sling, nylon, ac	Seat sling, nylon, adjustable, 1 bag											
LRT020000	0	Without seat sling												
Seat cushio	n, co	ver with zipper, blac	k											
LRT020101		Seat cushion, foam (medium-soft), cover with zipper, black, 3cm								£90				
LRT020102		Seat cushion, foam	Seat cushion, foam (medium-soft), cover with zipper, black, 5cm							£90				
LRT020103		Seat cushion, Latex	(very s	soft), c	over	with zi	ipper,	black	k, 5c	m				£90
Jay Cushior		complete Jay prod	uct rar	ige se	e Ja	y orde	r forr	ns						
JAY020002		Jay Basic												£75
JAY020001		Jay Easy Visco												£180
JAY020007		JAY Easy Fluid												£415
JAY020004		JAY Lite												£345
Seat access														
LRT090018	0	Lap belt with buckle	, metal											
	D 4													
Backrest h		CKREST	25	-30	20	-35	25	-40		0-45				
Back height	-	-	0	25	0	30	0	35	0		ı			
Dack neight	seun	g at (cm)	0	27.5	0	32.5	0	37.5	0	-				
			0	30	0	32.5	0	40	0	-				
			0	30	U	55	0	40	0	43				
LRT030001	•	Backrest tube, alum	inium										(Not for 250 mm backrest height)	
LRT030015	0													
		0 -1	2° (78	EU)		0	-8°	(82 E	EU)		0	-4° (86 EU)		
		0 0	° (90) I	EU)		0	4°	(94 E	U)		0	8° (98 EU)		
LRT030102														£90
		0 -1	2° (78	EU)		0	-8°	(82 E	EU)		0	-4° (86 EU)		
		0 0	° (90) I	ΞU)		0	4°	(94 E	U)		0	8° (98 EU)		
		Push handles												
LRT030201	٠	Push handles long												
LRT030203		Push handles, fold-o	lown									(only from back heig	ht 30cm; from 35 with angle adj back)	£170
LRT030204		Push handles, heigh	nt-adjus	stable									(only from back height 30cm)	£230
LRT030205		Push handles, heigh	nt-adjus	stable	for Ja	ay bac	ks						(only from back height 30cm)	£230
LRT030208		Push bar, height-ad	ustable	e, widt	h and	d angle	e-adju	stable	Э				(only from SW 28cm to 38cm)	£230
LRT030200	0	Without push handle	es											
		Backrest upholste	ry (bla	ck)										
LRT030316	0	EXO Backrest sling,	synthe	etic fib	re, pa	added,	adjus	stable	, 1 a	accesso	ory bag, black (Evo Exo Version)		
		Colour, binding tape	: •	Black	0	Orang	je C) Silve	ər	O Re	d O Blue			
LRT030317		EXO PRO Backr. sl	ng, syr	nthetic	fibre	, padd	ed, a	dj., br	eath	able sp	acer fabric, ac	cessory bag, black	(Evo Exo Version)	£195
		Colour, binding tape	: •	Black	0	Orang	je C) Silve	er	O Re	d O Blue			
LRT030300	0	Without backrest up	holster	у										
		Backrest accessor	ies											
LRT030411		Headrest, small heig	ght, de	oth an	d ang	gle-adj	ustab	le, 20	x 1	1cm		(only	with height adjustable push handles)	£270
LRT030410		Headrest, tall height	, depth	and a	angle	-adjust	table,	23 x	11ci	n		(only	with height adjustable push handles)	£270

		JAY BACKS plus ACCESSORIES - for complete Jay product range see Jay order forms	£
JAY 3 Back - I	Ποοι		
Upper Thoracio		□ JAY030021 Medium 46cm	£870
JAY030004	0.	Jay Flip Back Headrest (J3EUHDFH & J3EUHDLSP) (only with JAY 3 backs)	£290
JAY030006		□ Jay Std. Headrest (J3EUHDXH & J3EUHDLSP) (only with JAY 3 backs)	£235
	n Ba	ck - Shallow Contour (with fixed hardware)	2200
Low Thoracic:		□ JAY060001 Short - 17cm □ JAY060002 Tall - 24cm	£820
Mid Thoracic:		□ JAY060003 Short - 30cm □ JAY060004 Tall - 38cm	£820
JAY Zip Back			
M (20 cm)		□ JAY070004 SW 28cm	£725
M (20 cm)		□ JAY070005 SW 30-34cm	£745
T (25cm)		□ JAY070007 SW 28cm	£750
T (25cm)		□ JAY070008 SW 30-34cm	£765
X (30cm)		□ JAY070010 SW 28cm	£780
X (30cm)		□ JAY070011 SW 30-34cm	£795
		ARMREST AND SIDEGUARDS	
		Armrest (choose only one option, not in combination with sideguards; only with 0° and 1° camber)	
LRT040050		O Single post height adjustable armrest armpad short (25cm)	£195
LRT040051		O Single post height adjustable armrest Armpad long (36cm)	£195
LRT040052	0	Single-post sideguard, armpad (33cm), height-adjustable, remove (Not with abducted frame and COG 83)	
		Sideguards (not in combination with armrests)	
LRT040103	0	Aluminium sideguard, fender, wet weatherprotection (in frame colour) (1) (available with safari brake)	
LRT040107	0	Composite sideguard, removable (black) (not with safari brake)	
LRT040102		Aluminium sideguard, wet weatherprotection (in frame colour) (1) (not with safari brake)	£215
LRT040055		Armpad, height-adjustable, short (not with safari brake)	£215
LRT040104		Carbon fibre sideguard, fender, wet weatherprotection (black) (1) (not with safari brake)	£410
		TRAYS	
LRT090111		Tray, wood, elevated frame, push-fit, SW 22 - 36cm only with LRT040055	£185
LRT090112		Tray, plastic, swing-away, left-mount (only with height adj. armrests with pad)	£185
LRT090113		Tray, plastic, swing-away, right-mount (only with height adj. armrests with pad)	£185
	_	FRAME	
LRT010010		Frame FF 75 ° (integrated footrest)	
LRT010011		Frame FF 85 ° (integrated footrest)	
LRT010023		Frame FF 75° (integrated footrest), abducted (2.5cm on each side) (not for SW 48cm, Max User Weight 100kg)	0407
LRT010016 LRT010015		Frame FF 85 ° (integrated footrest), inset (2cm on each side), active (from SW 34cm)	£195
		Frame SA (removable footrest) (not for SD 32/34cm)	
LRT090100	•	Tie down brackets for transportation	
00022	0	CENTRE OF GRAVITY (COG) measured from front of back post; choose only one option	
COG23		Centre of gravity 2.3cm	
COG43		Centre of gravity 4.3cm	
COG63		Centre of gravity 6.3cm	
COG83		Centre of gravity 8.3cm dth (measured between the sideguards) is seat width + 2cm	

			£
		FRAME ACCESSORIES	
LRT010500		Wheelbase extension for add-on bike (not with drumbrake, crutch holder, tip assist, anti tip, wheel drive)	290
LRT090010		Transit wheels (not with crutch holder, tip assist and anti tip)	255
		Tip assist (step tube) & Crutch holder	
LRT090001		Tip assist, left LRT090002	35
LRT090003		Tip assist, pair (choose either tip assist or anti- tip tubes, not both)	105
LRT090009		Crutch holder, loop (only in combination with tip assist)	145
		Anti-tip tubes, swing-away	
LRT090036	0	Anti-tip tubes, aluminium, lightweight, swing-away (forwards), pair (not with tip assist)	
LRT090004		Anti-tip tubes, swing-away, left LRT090005	115
LRT090006		Anti-tip tubes, swing-away, pair (choose either tip assist or anti- tip tubes, not both)	235
		PREPARATION FOR ATTITUDE ADD-ON BIKE - only with FF-Frames	
LRT090211		without ATTITUDE order (docking pins assembled)	130
LRT090212	0	with ATTITUDE order (docking pins assembled; ATTITUDE order separatley)	
		HANGERS & FOOTPLATES	
		Aluminium hanger	
LRT050002	0	Hanger angle 70°	
LRT050001	0	Hanger angle 80°	
LRT050041	0	Hanger angle 90° (not with 6" & 7")	
LRT050006	0	Hanger, aluminium, swing-away, LH <i>LRT050007</i> O Hanger, aluminium, swing-away, RH	
pick both	0	Hanger, aluminium, swing-away, pair	
		Composite hanger	n
LRT050002	0	Hanger angle 70°	
LRT050001	0	Hanger angle 80°	
LRT050003	0	Hanger, composite, swing-away, LH LRT050004 O Hanger, composite, swing-away, RH	
pick both	0	Hanger, composite, swing-away, pair	
		Elevating Legrest (ELR) (not with footboards, platform; only SA frame)	
LRT050009			170
LRT050010		Hanger, aluminium, flip-up (0° - 90°), swing-away, RH	170
pick both		Hanger, aluminium, flip-up (0° - 90°), swing-away, pair (1)	340
		Footboard (when SA front selected)	
LRT050020	•	Footplates, divided, composite, angle-adjustable, flip-up (sideways), heel loop, black (2/5)	
LRT050050		Footplates, divided, aluminium, angle-adjustable, flip-up (sideways), heel loop, black (6)	145
LRT050102		Footboard, platform, aluminium, angle-adjustable, flip-up (sideways), heel loop, black	195
		LRT050126 Swing-away mechanism for platform footboard (from LLL 34cm)	135
107050404	<u> </u>	LRT050062 Locking system, platform footplate, aluminium	70
LRT050131 LRT050132	0	Footboard, platform, lightweight, composite, angle & depth-adjustable flip up (sideways), calf strap (2) Footboard, platform, lightweight, carbon, angle & depth-adjustable flip up (sideways), calf strap (7)	405
LRT050132			405 25
LITIOSOTZI		Adjustable side protection, to create a side-stop on the footboard Footboard (only with fixed front frame)	25
LRT050025	0		
LRT050025		Footboard, platform, lightweight, composite, angle and depth-adjustable, calf strap, black (3) Footboard, platform, lightweight, aluminium, angle and depth-adjustable, calf strap, black (3)	200
LRT050026		Footboard, platform, lightweight, carbon fibre, angle and depth-adjustable, call strap, black (3)	405
LRT050127		Adjustable side protection, to create a side-stop on the footboard	25
		LOWER LEG LENGTH (LLL) - LLL has to be 2.5cm lower than front seat height; measurements in cm	
		O 22 O 23 O 24 O 25 O 26 O 27 O 28 O 29 O 30	
		O 31 O 32 O 33 O 34 O 35 O 36 O 37 O 38 O 39	
		O 40 O 41 O 42 O 43 O 44 O 45 O 46 O 47	
LLL 22-29 fro	m SW	34 (SW30 with abduction) with divided footboard / from SW32 (SW28 with abduction) with platform footboard	
		ion with footboard platform; not with SW 28-36cm (2) from LLL 30cm	
(3) from LLL	. 28cm;	with FF frame 85°/75° from SW 30cm (4) not with SA frame	
(5) from SW	′ 36; wi	th inset from SW 40; with abduction from SW 32cm (6) with SA frame and FF frame 85°/75° from SW 30cm	
(7) from SW	′ 32cm;	with inset from SW 36cm	

		FORK (compare with your choice on the first page)	£
RT080041	0	Castor fork, Aluminium, Black	
	0	LRT080042 O Colour Cast. Fork Silver	
		LRT080043 ^O Colour Cast. Fork Orange	
RT080013	0	Castor fork, Carbotecture ® (only 111 mm)	
111000010	Ũ	Black O Orange O Silver O Red O Blue	
_RT080101		Expansion kit, designed for hemiplegic users (not with 7" castors, Carbotecture fork; SA frame only)	£14
		CASTOR (compare with your choice on the first page)	
.RT080301	0	Castor, solid (hard), rim: composite	
RT080302	0	Castor, solid (soft), rim: composite (only for 5" and 6")	
.RT080305	0	Castor, pneumatic, rim: composite (only for 4" and 5")	
RT080304		Castor, solid (hard), rim: aluminium (only for 4" and 5")	£10
LRT080306		Castor, solid (soft), rim: aluminium, silver (only for 4" and 5")	£100
		Colour, rim: LRT080311 O Black LRT080315 O Blue	
		LRT080313 O Orange LRT080314 O Red	
	_	REAR WHEELS (compare with your choice on the first page; choose only one wheel type)	
_RT070001	0	REAR WHEELS (compare with your choice on the first page, choose only one wheel type) Rear wheel, Universal, 36 spokes, cross-wise spokes	
_RT070002		Rear wheel, Design, 36 spokes, straight spokes (only 24")	
.RT070003	0		
_RT070004		Rear wheel, Proton, 24 spokes, straight spokes (Max User Weight 100kg)	£62
_RT070005		Rear wheel, Spinergy, 18 spokes (black), straight spokes; hub: silver (24" only)	£58
_RT070008			£47
.RT070401		Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation (not with camber; axle plate silver)	£87
		Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation (not with camber; axle plate silver)	£87
LRT070402			
LRT070000	0	Without rear wheel	
LRT070000		Without rear wheel	
LRT070000	0	Without rear wheel TYRES (choose only one tyre type)	
LRT070000 LRT070107 LRT070101	•	Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24")	
	•	Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (only 24")	£12
RT070000 RT070107 RT070101 RT070102	0 • 0	Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24")	£12
RT070000 RT070107 RT070101 RT070102 RT070104	0 0 0	Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (only 24") HANDRIM (only 24")	£120
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24") HANDRIM Handrims, stainless steel, silver	£12
LRT070000 LRT070107 LRT070101 LRT070102 LRT070104 LRT070204 LRT070202		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24") HANDRIM (and with lightweight wheels) Handrims, stainless steel, silver Handrims, aluminium, anodised, silver	£12
.RT070000 .RT070107 .RT070101 .RT070102 .RT070104 .RT070204 .RT070202 .RT070201		Without rear wheel Choose only one tyre type Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24") HANDRIM Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear	
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070202 RT070201 RT070203		Without rear wheel (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24") HANDRIM (and y24") Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear Handrims, aluminium, powder-coated, coloured	£80
LRT070000 LRT070107 LRT070101 LRT070102 LRT070104 LRT070204 LRT070202 LRT070201 LRT070203 LRT070207		Without rear wheel (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24") Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24") HANDRIM (and rims, stainless steel, silver Handrims, aluminium, andised, silver (and rims, aluminium, powder-coated, clear Handrims, aluminium, powder-coated, clear (and rims, supergrip (s) (22" only with universal and drum brake wheels) (22" only with universal and drum brake wheels)	£80 £29
LRT070000 LRT070107 LRT070101 LRT070102 LRT070104 LRT070204 LRT070202 LRT070201 LRT070203 LRT070207 LRT070208		Without rear wheel TYRES Tyre, pneumatic, slick, Schwalbe One Tyre, pneumatic, fine profile, Schwalbe Right Run Tyre, pneumatic, fine profile, Schwalbe Right Run Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24') HANDRIM Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear Handrims, Supergrip ® (22" only with universal and drum brake wheels) Handrims, Maxgrepp ®	£80 £29 £29
LRT070000 LRT070107 LRT070101 LRT070102 LRT070104 LRT070204 LRT070204 LRT070201 LRT070203 LRT070203 LRT070208 LRT070212		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (only 247) Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (aluminium, powder-coated, clear Handrims, Supergrip ® (22" only with universal and drum brake wheels) Handrims, Maxgrepp ® (ergonomic handrims with rubber-strip, 24" and 25" only)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070201 RT070203 RT070203 RT070207 RT070208 RT070212		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (only 247) Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (aluminium, powder-coated, clear Handrims, Supergrip ® (22" only with universal and drum brake wheels) Handrims, Maxgrepp ® (ergonomic handrims with rubber-strip, 24" and 25" only)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070201 RT070203 RT070207 RT070208 RT070212		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (only 247) Handrims, stainless steel, silver Handrims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (aluminium, powder-coated, clear Handrims, Supergrip ® (22" only with universal and drum brake wheels) Handrims, Maxgrepp ® (ergonomic handrims with rubber-strip, 24" and 25" only)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070202 RT070203 RT070203 RT070207 RT070208 RT070208 RT070212 RT070200		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24*) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24*) HANDRIM (not with lightweight wheels) Handrims, stainless steel, silver (and rims, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (22* only with universal and drum brake wheels) Handrims, Maxgrepp ® (argonomic handrims with rubber-strip, 24* and 25* only) Without handrims (ergonomic handrims with rubber-strip, 24* and 25* only)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070201 RT070203 RT070207 RT070207 RT070208 RT070212 RT070212 RT070200		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24*) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24*) HANDRIM (and right weight wheels) Handrims, stainless steel, silver (and right weight wheels) Handrims, aluminium, anodised, silver (and right weight wheels) Handrims, aluminium, powder-coated, clear (22* only with universal and drum brake wheels) Handrims, Maxgrepp ® (and right weight wheels) Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24* and 25* only) Without handrims (and right weight weight wheels)	£120 £80 £299 £299 £299
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070207 RT070207 RT070207 RT070208 RT070212 RT070212 RT070217 RT070317 RT070317 RT070327		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24') Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24') HANDRIM (only 24') Handrims, stainless steel, silver (and with lightweight wheels) Handrims, aluminium, anodised, silver (and with universal and drum brake wheels) Handrims, aluminium, powder-coated, clear (22' only with universal and drum brake wheels) Handrims, Supergrip @ (22' only with universal and drum brake wheels) Handrims, Balipse 3R, black (ergonomic handrims with rubber-strip, 24" and 25" only) Without handrims (not with Maxgrepp) HAND RIM MOUNTING (not with Maxgrepp)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070207 RT070207 RT070207 RT070208 RT070208 RT070212 RT070212 RT070317 RT070317 RT070327		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 24) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 24) HANDRIM (and rims, stainless steel, silver Handrims, stainless steel, silver (and rims, aluminium, nondised, silver Handrims, aluminium, powder-coated, clear (22° only with universal and drum brake wheels) Handrims, Bupergrip ® (and rims, Stippergrip ® Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24° and 25° only) Without handrims (not with Maxgrepp) Handrim mount, narrow (17 mm) (1) (not with Maxgrep) Handrim mount, super narrow (7 mm) (1) (Only with 24° stainless steel)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070204 RT070204 RT070201 RT070203 RT070207 RT070207 RT070212 RT070212 RT070212 RT070317 RT070317 RT070327 RT070307		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (only extra the state) Handrims, stainless steel, silver (andrimin, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (22° only with universal and drum brake wheels) Handrims, Supergrip @ (22° only with universal and drum brake wheels) Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24° and 25° only) Without handrims (1) (not with Maxgrepp) Handrim mount, narrow (17 mm) (1) (only with 24° stainless stee) Handrim mount, super narrow (7 mm) (1) (Only with 24° stainless stee) WHEEL CAMBER (choose only one option)	£80 £29 £29
RT070000 RT070107 RT070101 RT070102 RT070104 RT070104 RT070202 RT070201 RT070203 RT070207 RT070207 RT070208 RT070207 RT070208 RT070212 RT070200 RT070212 RT070317 RT070317 RT070327 RT070307		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (not with lightweight wheels) Handrims, stainless steel, silver (and rims, aluminium, anddised, silver Handrims, aluminium, powder-coated, clear (and rims, supergrip ® Handrims, Supergrip ® (22° only with universal and drum brake wheels) Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24° and 25° only) Without handrims (not with Maxgrep) Handrim mount, narrow (17 mm) (1) (not with Maxgrep) Handrim mount, wide (27 mm) (lony with 24° stainless steel) WHEEL CAMBER (choose only one option) Camber 0° (no camber brackets provided)	£80 £29 £29
LRT070000 LRT070107 LRT070101 LRT070102 LRT070104 LRT070204 LRT070202 LRT070201 LRT070203 LRT070207 LRT070208		Without rear wheel TYRES (choose only one tyre type) Tyre, pneumatic, slick, Schwalbe One (only 247) Tyre, pneumatic, fine profile, Schwalbe Right Run (not with lightweight wheels) Tyre, puncture proof, tread (not with lightweight wheels) Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution (only 247) HANDRIM (only extra the state) Handrims, stainless steel, silver (andrimin, aluminium, anodised, silver Handrims, aluminium, powder-coated, clear (22° only with universal and drum brake wheels) Handrims, Supergrip @ (22° only with universal and drum brake wheels) Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24° and 25° only) Without handrims (1) (not with Maxgrepp) Handrim mount, narrow (17 mm) (1) (only with 24° stainless stee) Handrim mount, super narrow (7 mm) (1) (Only with 24° stainless stee) WHEEL CAMBER (choose only one option)	£80 £29 £29

							£
		SPOKE GUARDS			(not with spinerg	y wheels)	
LRT070831		Transparent	LRT070813		Glaktica LRT070828 Space		£160
LRT070823		Princess	LRT070821		Pirates		£160
LRT070816		Happy Lions	LRT070814		Graffiti		£160
LRT070819		Monkeys	LRT070802		Basketball		£160
LRT070820		Oriental	LRT070812		Flying Water		£160
LRT070829		Superhero	LRT070833		Zebra		£160
LRT070817		Hot Wheels	LRT070818		Jungle Fever		£160
LRT070822		Pool	LRT070811		Feather		£160
LRT070827		Silk	LRT070806		Chrome		£160
LRT070830		Tiger	LRT070803		Basketball 2		£160
		WHEEL LOCKS			(choose only o	ne option)	
LRT060001	0	Standard brake			(in combination with SA frame short and 24" wheel -> only with	COG 2.3)	
LRT060003	0	Compact brake			(not with abducti	on frame)	
LRT060013	0	Push to lock brake, integrated	in sideguard, S	afari			
LRT060002	0	Knee-lever brake					
LRT060010		□ Brake lever extension, kr	ee-lever brake	, folc	-down		£50
		ACCESSORIES					
LRT090000	•	Tool kit					
LRT090025		Air pump					£20
LRT090024		High pressure pump (0 - 14 ba	r)				£95
LRT090030		Back pack					£80
LRT090026		Mobile phone pocket					£60
		COLOURS ⁽¹⁾ Please con	sult our colour	cata	ogue to review your colour choice		
		Frame Handrim		For		Hub/rim	Fork
			£230	£75		£230	£75

	COLOURS	Please	consult our colo	ur catalogu	e to review your colour choice	9			
	Frame	Handrim	Hub/rim	Fork		Frame	Handrim	Hub/rim	Fork
			£230	£75				£230	£75
02 Brilliant Silver	0				29 Black	0			
03 Silver Matt	0				31 Matt Black	0			
06 Sun Yellow	0				32 Signal White	0			
14 Blue	0				33 Pink	0			
15 Brilliant Marine	0				34 Dark Chocolate	0			
16 Matt Marine	0				35 Skyblue	0			
19 Brilliant Purple	0				36 Cyan-Metallic	0			
21 Red Ruby	0				37 Marsred (Orange)	0			
22 Brilliant Red	0				40 Kiwi	0			
23 Matt Red	0				41 Flamingo-Glitter	0			
24 Tutti Frutti Orang	je O				42 Matt-Anthracite	0			
27 Graphite metallic	; 0				46 Mamba Green	0			
(1) Handrim: only w	ith handrim co	lour powder coa	ated; Hub/rim: only	for universa	wheel; Fork: not with Carbotect	ure			

			£
		STICKER COLOURS	
LRT100550	٠	Sticker colour - black	
LRT100551	0	Sticker colour - silver	
		ANODISED COLOUR AXLE PLATE (not in combination with one hand operation)	
LRT100580	0	Axle plate anodised, black	
LRT100581	0	Axle plate anodised, silver	
LRT100582	0	Axle plate anodised, orange	
		24 " LIGHT WEIGHT WHEEL COLOURS	
	٠	Black	
LRT100336		Anodised, orange	£120
LRT100337		Anodised, blue	£120
LRT100338		Anodised, red	£120
Comment	s for	special build - please apply for a quote; lead time conditions my change.	
Quickia		PT Basis Brico	
		RT - Basic Price £2,195	
Option pric	e		
Option pric Packaging	e and		
Option pric Packaging Exclusive	e and		
Option pric Packaging	e and /AT		

Please follow this measuring method:

The following method is recommended on the basis of extensive practical experience. Deviations are possible in individual instances.

Seat width (SW): a) For the user: Allow space between sideguard and hip on each side of the chair (approx. 10 - 20 mm altogether) b) On the wheelchair: From outside frame tube to outside frame tube. Seat depth (SD): a) For the user: When sitting upright: leave space for 2 - 3 fingers between front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Fort seat height: From back of knee to bottom of shoe sole. a) For the user: When sitting with 90° kneeangle: a) For the user: When sitting with 90° kneeangle: b) On the wheelchair: From back of knee to bottom of shoe sole. b) On the wheelchair: From back of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. B) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: a) For the user: From back of seat tube to upper edge of backrest upholstery. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. <th>ç</th> <th></th>	ç	
(approx. 10 - 20 mm altogether) b) On the wheelchair: From outside frame tube to outside frame tube. Seat depth (SD): a) For the user: When sitting upright: leave space for 2 - 3 fingers between front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From font of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: a) For the user: b) On the wheelchair: From back of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Back height: a) For the user: b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: a) For the user: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angl	Seat width (SW):	
b) On the wheelchair: From outside frame tube to outside frame tube. Seat depth (SD): a) For the user: When sitting upright: leave space for 2 - 3 fingers between front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From back of knee to bottom of shoe sole. From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery.	a) For the user:	Allow space between sideguard and hip on each side of the chair
Seat depth (SD): a) For the user: When sitting upright: leave space for 2 - 3 fingers between front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: b) On the wheelchair: From back of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: b) On the wheelchair: From back of seat tube to the ground. Note: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: <		(approx. 10 - 20 mm altogether)
a) For the user:When sitting upright: leave space for 2 - 3 fingers between front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery.b) On the wheelchair:From back tube to front of seat upholstery.Front seat height: a) For the user:When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. From back of knee to bottom of shoe sole. b) On the wheelchair:From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height.Rear seat height: a) For the user:From back of seat tube to the ground. Note:Mote: Max. seat height difference rear to front is 130 mmBack height: a) For the user: b) On the wheelchair:From back of seat tube to upper edge of backrest upholstery.Note:Max. seat height difference rear to front is 130 mmBack height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	b) On the wheelchair:	From outside frame tube to outside frame tube.
front edge of the seat upholstery and back of knee. (approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: From back of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Back height: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	Seat depth (SD):	
(approx. 30 - 60 mm). Care must be taken with adj. upholstery. b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	a) For the user:	When sitting upright: leave space for 2 - 3 fingers between
b) On the wheelchair: From back tube to front of seat upholstery. Front seat height: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°		front edge of the seat upholstery and back of knee.
Front seat height: a) For the user: When sitting with 90° kneeangle: From back of knee to bottom of shoe sole. b) On the wheelchair: From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height. Rear seat height: b) On the wheelchair: From back of seat tube to the ground. Note: b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°		(approx. 30 - 60 mm). Care must be taken with adj. upholstery.
a) For the user:When sitting with 90° kneeangle: From back of knee to bottom of shoe sole.b) On the wheelchair:From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height.Rear seat height: b) On the wheelchair:From back of seat tube to the ground. Note:Mote:From back of seat tube to the ground. Note:Back height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.Back height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.Back neight: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.Back neight: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.Back neight: a) For the user: b) On the wheelchair:From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	b) On the wheelchair:	From back tube to front of seat upholstery.
b) On the wheelchair:From back of knee to bottom of shoe sole.b) On the wheelchair:From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height.Rear seat height: b) On the wheelchair:From back of seat tube to the ground. Note:b) On the wheelchair:From back of seat tube to the ground. Note:Back height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note:b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note:b) On the wheelchair:Important: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	Front seat height:	
b) On the wheelchair:From front of seat tube to the ground. (min. 30 mm longer than user measurement) Remember to include the cushion height.Rear seat height: b) On the wheelchair:From back of seat tube to the ground. Note:Back height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note:The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	a) For the user:	When sitting with 90° kneeangle:
Rear seat height: b) On the wheelchair:From back of seat tube to the ground. Note:Max. seat height difference rear to front is 130 mmBack height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note:The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°		From back of knee to bottom of shoe sole.
Rear seat height: b) On the wheelchair: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: b) On the wheelchair: Important: The back height depends on the degree of disability. O° is the angle 90° to the ground. Negative angles are < 90°	b) On the wheelchair:	From front of seat tube to the ground.
Rear seat height: b) On the wheelchair: From back of seat tube to the ground. Note: From back of seat tube to the ground. Note: Max. seat height difference rear to front is 130 mm Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°		(min. 30 mm longer than user measurement)
b) On the wheelchair:From back of seat tube to the ground. Note:Back height: a) For the user: b) On the wheelchair:From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerablyBack angle:Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°		Remember to include the cushion height.
Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	Rear seat height:	
Back height: a) For the user: From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade. b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	b) On the wheelchair:	From back of seat tube to the ground.
 a) For the user: b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90° 		Note: Max. seat height difference rear to front is 130 mm
b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery. Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	Back height:	
Note: The user's ability to sit upright has a major influence on the back height and it can therefore differ considerably Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	a) For the user:	From the seat, including cushion, to be no more than 10 - 20 mm below the lower shoulder blade.
Back angle: Important: The back height depends on the degree of disability. 0° is the angle 90° to the ground. Negative angles are < 90°	b) On the wheelchair:	From back of seat tube to upper edge of backrest upholstery.
Back angle:Important: The back height depends on the degree of disability.0° is the angle 90° to the ground. Negative angles are < 90°		Note: The user's ability to sit upright has a major influence on the
0° is the angle 90° to the ground. Negative angles are < 90°		back height and it can therefore differ considerably
	Back angle:	Important: The back height depends on the degree of disability.
and positive angles are > 90°.		0° is the angle 90° to the ground. Negative angles are < 90°
		and positive angles are > 90°.

Technical Data Overview - Life RT:

Max. overall height:	950 mm		
Max. overall length:	1075 mm		
Max. turning circle:	700 mm		
Max. safe slope:	10°		
Wheelchair weight:	from 10 kg		
Dismantled weight:	from 8 kg		
Weight of heaviest part:	2,1 kg		
Max. overall width:	Camber	22" rear wheel	24" rear wheel
	For 0° camber:	SW + 200 mm	SW + 200 mm
	For 3° camber:	SW + 230 mm	SW + 240 mm
	For 6° camber:	SW + 250 mm	SW + 260 mm

Product is **crash tested according to ISO 7176-19** and therefore approved for transportation in a vehicle For transport without a user the chair must be safe clamped in the vehicle

All changes in the configuration might change the seat heights. Manufacturing tolerances of +/- 10 mm

BACKREST



Backrest tube, aluminium Austauschen Life T



Backrest, angle adjustable



Push handles long



Push handles, fold-down



Push handles, height-adjustable



Without push handles,



Push bar, heightadjustable, width and angleadjustable



Headrest, height, depth and angle adjustable



EXO backrest sling



EXO PRO backrest sling



FRAME ACCESSORIES



Wheelbase extension for

add-on bike



Transit wheels



Tip assist



Crutch holder, loop



Anti-tip tubes, swing-away, left

HANGERS AND FOOTPLATES



Aluminium hanger, 90°



Composite hanger 110°/100°



Elevating legrest (ELR)



Footboard, divided, composite, angleadjustable, flip-up (sideways), heel loop, black



Footboard, platform, lightweight, plastic, angle and depthadjustable, calf strap, black



Footboard, divided, aluminium, angleadjustable, flip-up (sideways), heel loop, black



Footboard, angle and depth adjustable;flip up, aluminium with locking system



Footboard, platform, aluminium, angleadjustable, flip-up (sideways), heel loop, black



Footboard, platform, lightweight, plastic, angle & depth-adjustable flip up (sideways), calf strap



OF_QUICKIE_LIFE_RT_RIGIDTEENS_RETAIL_01.01.2024_REV1

QMP01

WHEEL LOCKS



Standard brake



Knee-lever brake



Compact brake



Push to lock brake, integrated in sideguard, Safari



Push to lock brake, onearm, right actuation



Brake lever extension, knee-lever brake, folddown

ACCESSORIES



Back pack



High pressure pump

Air pump



Mobile phone pocket

ANODIZED COLOUR AXLE PLATE





Axle plate anodized, orange

Axle plate anodized, silver



24 " LIGHT WEIGHT WHEEL COLOURS



Lightweight wheel, anodized orange



Lightweight wheel, anodized blue



Lightweight wheel, anodized red