



# Easy Life i

	_											_											2.24
Deliver to: lame: street: own: -Mail: el:		Postal code: Fax:						(	€		Deliv Name Street Town E-Ma Tel:	et: n:							Pos	tal co	de:		
order date:													Mark	ed for	:								
urchase c													C			_							
lumber red	quire	a:											Sunr	ise ord	ndard						П	- Co	st option
□ Or	der		Calcula	tion	□ Buil	t 4 me	Э						./.	= Pric			ı						cost opt
Reimb	ours	emei	nt code	a:									Max	. use	r wei	aht:							140 kg
Art. no														R WE		-			ı				kq
AIL III	J O	4500	003											tory info	-		ire corre	ct confi	<b>l</b> guration				Ng
														. ,				e Pr	_				
					CLIE	NIT M	I	CLIDE	- NAIT-I	NTC	/all 100			m40	المالة المالة	امريما	-i\						
					CLIE	NIN	IEA:	SURE		NI 5	(all m	ieasu	reme	nts w	itnou	CUSI	nion)						
SE	AT V	VIDT	H SELE	CTION -	measure	ed in r	mm	from c	outsio	de fra	me tul	be to	outsid	le fran	ne tub	е							
	3	40	360	380	400	420	0	44	0	40	60	4	80	50	00	52	20	54	40				
		0	0	0	0	0																	
	ь			Ü	U	U		0		(	)		)	(	)	(	)	(	)				
SE	_				- measur			0		(	)	•	0	(	)	(	O	(	)				
SE	AT E	DEPT Sh	H SELE	ECTION -	- measur Mediur	ed in ı	mm					Long	frame	)					D.				
SE	AT [	Sh	H SELE nort fram 380	ECTION -	measur Mediur 420	ed in in fram	mm ne	46	0	4	B0	Long 5	frame	52	20	54	40	(	D.				
SE	AT [	Sh 60	H SELE	ECTION - ne 400	measure Mediur 420	ed in in fram	mm ne 0	46	0	41	<b>80</b>	Long 5	frame	52	20	54	<b>40</b>		D.				
SE	AT [	Sh 60	H SELE	ECTION -	- measure - Mediur - 420 - O - 360-420	ed in 1  n fram  440  420-4	mm ne 0	46	<b>0</b>	440	<b>80</b> O -480	<b>Long 5</b> 440	frame	52	20	54	40		D.				
	360	Sh 60 0	H SELE nort fram 380 0 360-400	ECTION - ne   400   ○ 360-400	- measure - Mediur - 420 - O - 360-420	ed in I	mm 0 140 t dep	<b>46</b> ○ 440-₄ th adjus	<b>0</b> 480 stmen	440 440 t via se	BO O -480 eat sling	Long 5 440 3 (1)	frame 00 00 -500	52	<b>20</b>	54	<b>40</b>		D.				
	360	Sh 60 0	H SELE nort fram 380 0 360-400	ECTION - ne   400   ○ 360-400	- measure Mediur 420 O 360-420 Qui	ed in I	mm  140 t dep	<b>46</b> ○ 440-₄ th adjus	0 480 stmen	440 440 t via se	BO D -480 eat sling	Long 5 440 3 (1)	frame 00 00 -500	52	<b>20</b>	54	<b>40</b>		D.				
	360	Sh 60 0 1-380	H SELE nort fram 380  360-400	ECTION - ne   400   ○ 360-400   SHT SEL	- measure Mediur 420 O 360-420 Qui	ed in Infram 440 0 420-4 ick seat	mm  140 t dep	460-440-4th adjust	0 480 stmen	440 440 t via se ront cont in m 420	BO C -480 eat sling astors nm 430	440 440 440	frame 00 00 -500	52	<b>20</b>	54	<b>40</b>	500	510	520	530	540	
	360	Sh 60 0 1-380	H SELE nort fram 380  360-400  AT HEIG  Ork type Hemi Ve	### SEL (mm)	Mediur 420 O 360-420 Qui	ed in I	mm  140 t dep	460-440-4th adjust	0 480 stmen	44 440 t via se	B0  -480 eat sling astors nm  430	Long 5 440 440 6, and	frame 00 -500 frame	440: 440: 460	20 -520 ons	54 (440)	40 -540 490			520	530	540	
	3 360	Sh 60 0-380 SEA Alun	H SELE  ort fram  380  360-400  AT HEIG  ork type  Hemi Ve  ninium (1	### SEL (mm)   43mm)	- measur Mediur 420 ○ 360-420 Qui	ed in I	mm  140 t dep	460-440-4th adjust	0 480 stmen	440 440 t via se ront cont in m 420	BO C -480 eat sling astors nm 430	440 440 440	frame	440: 440: 460	20 -520 ons	440	40 -540 490	500			530	540	
	360	SEA Alun Alun Alun	H SELE nort fram 380  360-400  THEIG  THEIG  Hemi Ve ninium (1	### SEL (mm)   168mm)	Mediur 420 O 360-420 Qui	ed in I	mm  d440 t deprepen	460-440-4th adjust	0 480 e of fr	440 440 t via se	astors	Long 5 440 (1) 440 0	frame 00 0-500 frame 450	440: 440: 460	20 D520 Sons	54 (440)	40 -540 490			520	530	540	
FR	33 360 ONT	SEA FOR Alun Alun Alun Alun	H SELE ort fram 380 360-400  AT HEIG ork type Hemi Ve ninium (1 ninium (1	### SEL ### (### ### ### ### ### ### ### ### #	Mediur 420 O 360-420 Qui	ed in in fram 440 420-4 ick seal	mm  140 t dep	460-440-4th adjust	0 480 stmen e of fr heigh	440 440 t via se	80 -480 eat sling asstors nm 430 O	440 6, and	frame 00 0-500 frame 450	440 440 460	20 D520 Sons 470	480 	40 >-540 490 O	500	510		530	540	
FR	33 360 ONT	Shape	H SELE nort fram 380  360-400  THEIG  THEIG  Hemi Ve ninium (1	### SEL (mm) (143mm) (168mm) (168mm)	Mediur 420  360-420 Qui  ECTION:	ed in in fram 440 420-4 ick seal	mm  d440 t deprepen	460-440-4th adjust	0 480 e of fr	440 440 t via se	astors	Long 5 5 (440 440 ) . , and	frame 00 0-500 frame 450	440: 440: 460	20 D520 Sons	440	40 -540 490	500			530	540	
FR	33 360 ONT	Shape	H SELE ort fram 380 360-400  THEIG ork type Hemi Ve ninium (1 ninium (1 ninium (1	ECTION - ne	Mediur 420  360-420 Qui  ECTION:	ed in I m fram 440 420-4 420-4 in I de F F a grant a g	mm  d440 t deprepen	460-440-4th adjust	0 480 stmen e of fr heigh	440 440 t via se	astors  430  0	440 6, and	frame 00 -500 frame 450	440 440 460	20 D520 Sons 470	480 	40 >-540 490 O	500	510		530	540	
FR	33 360 ONT	Shadow SEA	H SELE nort fram 380  360-400  AT HEIG  Ork type Hemi Ve ninium (1 ninium (1 ninium (1 Hemi Ve	### SEL #### SECTION - 1	- measure  Mediur  420  360-420  Qui  ECTION:  Frame  Standa	ed in I m fram 440 420-4 420-4 in I de F F a grant a g	mm  d440 t deprepen	460-440-4th adjust	0 480 stmen e of fr heigh	440 440 t via se	880	Long 5 4440 440 0 0 0 0 0 0 0	frame 00 -500 frame 450	553 (4400 4400 4400 4400 4400 4400 4400 44	20 D) -5-520 Ons 470 O O O	480 0 0	490 O	500	510		530	540	
	33 360 ONT	Shadow SEA	H SELE nort fram 380  360-400  AT HEIG  ork type Hemi Ve ninium (1 ninium (1 ninium (1 ninium (1) ninium (1)	### SEL #### SEL #######################	Mediur 420 O 360-420 Qui  ECTION: Frame Standa Neuro	ed in Inframe 44(	mm  d440 t deprepen	460-440-4th adjust	0 480 stmen e of fr heigh	440 440 t via se	880	Long 5 4440 440 0 0 0 0 0 0 0	frame 00 -500 frame 450	440 version o	200 ONS	480 0 0	490 -540	0	510	0		540	
FR	33 360 ONT	SEA  SEA  Alun Alun Alun Alun Alun Alun Alun Al	H SELE  ort fram 380  360-400  AT HEIG  ork type Hemi Ve ninium (1 ninium (1 ninium (1 ninium (1 ninium (1 ninium (1) ninium (1) ninium (1)	### SEL  ###	- measure  Mediur  420  360-420  Qui  ECTION:  Frame  Standa	ed in Inframe 44(	mm  d440 t deprepen	460-440-4th adjust	of fright	440 (440 440 440 440 440 440 440 440 440	880	440 O O O O O O	frame   000  -500   frame   450   O	440	200	480 0 0	490 -540	0	510	0		540	
FR	33 360 ONT	SEA  SEA  Alun Alun Alun Alun Alun Alun Alun Al	H SELE Nort fram 380 360-400  AT HEIG  Ork type Hemi Ve ninium (1 ninium (1 hemi Ve nininium (1 hemi Ve ninium (1 hemi Ve ninium (1 hemi Ve	### SEL  ###	Mediur 420 O 360-420 Qui  ECTION: Frame Standa Neuro	ed in Inframed A4(	mm  d440 t deprepen	460-440-4th adjust	oo 480 480 of fright	440 (440 t via se	### ##################################	440 O O O O O O O O O O O O O O O O O O	frame  450  0  0  0  0  0  0  0	9 55 (440) (	470 0 0 0	480	490	500 ○	510	0		540	

**REAR SEAT HEIGHT SELECTION:** in dependance of rear wheel size

Rear seat height in mm

Rear wheels	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510
22"	0	0	0	0	0	0	0	0	0	0	0	0			
24"				0	0	0	0	0	0	0	0	0	0	0	0

The rear seat height can only be between 0 cm and 11 cm below the selected front seat height.

(1) Additionally to the seat depth adjustment via the seat sling the seat depth can be adjusted with tools via the back tube by +4 cm except of SD 520 & 540 mm

For more information © Sunrise Medical 2024

#### Please follow this measuring method:

The following method is recommended on the basis of extensive practical experience. Deviations are possible in individual instances.

Seat width (SW):

a) For the user: Allow space between sideguard and hip on each side of the chair

(approx. 10 - 20 mm altogether)

b) On the wheelchair: From outside frame tube to outside frame tube.

Seat depth (SD):

a) For the user: When sitting upright: leave space for 2 - 3 fingers between

front edge of the seat upholstery and back of knee

(approx. 30 - 60 mm). Care must be taken with adj. upholstery.

b) On the wheelchair: From back tube to front of seat upholstery.

Front seat height:

a) For the user: When sitting with 90° kneeangle:

From back of knee to bottom of shoe sole.

b) On the wheelchair: From front of seat tube to the ground .

(min. 30 mm longer than user measurement) Remember to include the cushion height.

Rear seat height:

b) On the wheelchair: From back of seat tube to the ground.

Note: Max. seat height difference rear to front is 130 mm

Back height:

a) For the user: From the seat, including cushion, to be no more than 10 - 20 m 69
b) On the wheelchair: From back of seat tube to upper edge of backrest upholstery.

**Note:** The user's adility to sit upright has a major influence on the

back height and it can therefore differ considerably

**Back angle:** Important: The back height depends on the degree of disability.

 $0^{\circ}$  is the angle  $90^{\circ}$  to the ground. Negative angles are <  $90^{\circ}$ 

and positive angles are > 90°.

#### **Technical Data Overview:**

Max. overall height: 1125 mm

Max. overall length: 1190 mm

Max. turning circle: 960 mm

Max. safe slope: 10°

Wheelchair weight: from 14,5 kg

Dismantled weight: from 8 kg

Weight of heaviest part: 2,1 kg

Max. overall width: Camber 22" rear wheel 24" rear wheel

For  $0^{\circ}$  camber: SW + 200 mm SW + 200 mm For  $3^{\circ}$  camber: SW + 270 mm SW + 280 mm

Product is crash tested accoring to ISO 7176-19 and therefore approved for transportation in a vehicle

For transport wihout a user the chari must be safe clamped in the vehicle

All changes in the configuration might change the seat heights.

Manufacturing tolerances of +/- 10 mm

	•	= Standard O = No cost option □ = Cost option	Price in €
		SEAT UPHOLSTERY AND CUSHIONS	
.11020009	•	Seat slings	1
.11020009	0	Seat sling adjustable, with one utility bag (bottom cavity adjustable, depth adjustable)	+
.11020000		without seat sling	1
		Seat cushion, cover with zipper, black	
.II020101		Seat cushion, foam (medium-soft), cover with zipper, black, 30 mm	
II020102		Seat cushion, foam (medium-soft), cover with zipper, black, 50 mm	
		Jay Cushion - for complete Jay product range see Jay order forms	
AY020002		Jay Basic	1
AY020003		Jay Soft Combi P	
AY020001		Jay Easy Visco	
AY020007		JAY Easy Fluid	
AY020004		JAY Lite	
			1
		Seat accessories Seat accessories	_
11090018		Positioning belt	
		BACKDEST	
		BACKREST Fixed back	
II030021	•	Fixed back with long push handles	1
1103002 1		Fixed back with integrated height adjustable push handles	
11030207		O 410 mm back height	
		O 435 mm back height	
		O 460 mm back height	
11030061		Fixed back, 90°, long push handles	+
1030001		O 375 mm	
		O 400 mm	
		O 425 mm	
		0 423 11111	
		Angle adjustable back with long push handles	
11030023		Angle adjustable back with long push handles -5° to 25°	
11030025		Angle adjustable back with offset height adj push handles	
Back height i	range	360 - 400 mm 400 - 450 mm 450 - 500 mm	
		O 360 mm back height O 400 mm back height O 450 mm back height	
		O 375 mm back height O 425 mm back height O 475 mm back height	
		O 400 mm back height O 450 mm back height O 500 mm back height	
		Reclining back with long push handle	
1030014		Reclining back with long push handles (back angle range 0 - 30°) (back height 480 mm only	)
	_	Backrest upholstery (black)	_
11030316	0	EXO Backrest sling, synthetic fibre, padded, adjustable, 1 accessory bag, black	
		Colour, binding tape: ● Black ○ Orange ○ Silver ○ Red ○ Blue	
11030317		EXO PRO Backr. sling, synthetic fibre, padded, adj., breathable spacer fabric, accessory bag, black	
	_	Colour, binding tape: ● Black ○ Orange ○ Silver ○ Red ○ Blue	
1030300	0	Without backrest upholstery	
		Backrest accessories	
11030402		Autofolding stabilizer bar (only from SW 360 mm	))
11030411		Headrest, medium height, depth and angle-adjustable, 20x11cm (not with LII030402; only from SW 380 mm	-
		Headrest, tall height, depth and angle-adjustable, 23x11cm (not with LII030402; only from SW 380 mm	))
11030410			

### **SEAT UPHOLSTERY AND CUSHIONS**



Seat cushion, cover with zipper, black



Seat cushion, climate membrane water-resistant, cover with zipper, black



Positioning belt with lock



Jay Basic (picture shown without upholstery)



Jay Soft Combi P (picture shown without upholstery)



Jay Easy Visco (picture shown without upholstery)



Jay Easy Fluid (picture shown without upholstery)



Jay Lite



# **BACKREST**



Fixed back



Angle adjustable back



Reclining back



Trunk support



Headrest



LII030316 EXO backrest sling (EXO Evo version)



LII030316 EXO backrest sling (EXO Evo version)

© Sunrise Medical 2024

Life i			
	•	= Standard O = No cost option □ = Cost option	Price in €
		JAY BACKS plus ACCESSORIES - for complete Jay product range see Jay order form	S
_		Contour (MC)	
Mid Thoracic: Upper Thorac		□ JAY030013 Short - 420 mm □ JAY030020 Medium - 340 mm □ JAY030018 Tall - 380 □ JAY030013 Short - 420 mm □ JAY030020 Medium - 460 mm □ JAY030026 Tall - 500	
Shoulder Heid		□ JAY030016 Short - 530 mm □ JAY030023 Medium - 570 mm □ JAY030029 Tall - 610	
,		Deep Contour (MDC) (150 mm contour depth)	
Mid Thoracic:		☐ JAY030044 Medium - 340 mm ☐ JAY030041 Tall - 380	mm
Upper Thorac	cic:	☐ JAY030045 € Short - 420 mm ☐ JAY030042 Medium - 460 mm ☐ JAY030046 Tall - 500	mm
Shoulder Heig	ght:	□ JAY030043 Short - 530 mm □ JAY030047 Medium - 570 mm □ JAY030048 Tall - 610	mm
		Deep Contour (Extra Deep, 180 mm contour depth)	
Mid Thoracic:		☐ JAY030049 Tall - 380	mm
Upper Thorac		☐ JAY030050 Medium - 570 mm	
Jay 3 Back - Upper Thorac		□ JAY030014 Short - 420 mm □ JAY030021 Medium - 460 mm □ JAY030027 Tall - 500	mm
Shoulder Heigh		□ JAY030017 Short - 530 mm □ JAY030024 Medium - 570 mm □ JAY030030 Tall - 610	
	_	osterior Deep Contour	
Mid Thoracic:		□ JAY050037 Tall - 380	mm
Upper Thorac	cic:	□ <i>JAY050031</i> Medium - 460 mm	
Shoulder Heig	ght:	☐ <i>JAY050032</i> Short - 530 mm	
WHT030415		□ Whitmyer Headrest, COBRA XTRA, Flip back (only with JAY J3 to 1)	
WHT030416		□ Whitmyer Headrest, AXYS, Standard (only with JAY J3 in	Backs)
		ARMREST AND SIDEGUARDS	
		Armrest (choose only one option, not in combination with sidequards; only with 0° ca	amber)
LII040053	0	Armrest tool height adjustable, short/long (not with reclining	
LII040054		Height adjustable armrest with long and short pad sliding (not with reclining	g back)
LII040110		☐ Hemi armpad XL (length: 540 mm; width: 135 mm) (added; left & right to	ısable)
LII040111		☐ Hemi armpad small (length: 460 mm; width: 105 mm) (added; left & right to	ısable)
		Height adjustable armrest, one hand operation (not with reclining	j back)
LII040058		☐ Armpad short (250 mm)	
LII040059		☐ Armpad long (310 mm)	
LII040050		Single post height adjustable	
LII040050 LII040051		O Short armpad (250 mm) O Long armpad (360 mm)	
LII040052		Single post tool height adjustable, short & long armpad - length adjustable	
1.110.40.10.7		Sideguards (not in combination with an Composite detachable	mrest)
LII040107 LII040102		Aluminium without fender (not with re	acliner)
LII040103		Aluminium with fender (not with re	
		,	
		FRAME	
LII010015	0	Standard frame	
LII010017		Neuro frame	
LII090100		Crash test option (required to use the chair as seat in	a car)
		CENTER OF GRAVITY (COG) measured from front of back post; choose only one option	
L11070500	0	Centre of gravity -50 mm (rear wheel extension)  (not with one arm	n drive)
COG00	0	Centre of gravity 0 mm (not with one arm	n drive)
COG10	0	Centre of gravity 10 mm (not with one arm	ı drive)
COG20	0	Centre of gravity 20 mm (not with one arm	ı drive)
COG30	0	Centre of gravity 30 mm	
COG40	0	Centre of gravity 40 mm (not with one arm	
COG50	0	Centre of gravity 50 mm (not with one arm	i drive)
		FRAME ACCESSORIES	
LII090010		Transit wheels (pair) (not with crutch holder, tip assist and swing away a	anti tip)
LII090001		Tip assist & crutch holder (1)  Tip assist left	<del>-   -  </del>
LII090001		Tip assist telt  Tip assist pair	<del></del>
L11090009		Crutch holder (only in combination with tip	assist)
		(5.3)	
(1) Two anti tip	tubes	swing away cannot be combined with tip assist.	For more information
			www.SunriseMedical.eu
			© Sunrise Medical 2024

### **JAY BACKS**



Jay 3 Back Mid Contour



Jay 3 Back Mid Deep Contour



Jay 3 Back Deep Contour

# ARMREST AND SIDEGUARDS



Armrest tool height adjustable



Height adjustable armrest with long/short pad



Single post height adjustable



Single post tool height adjustable



Hemi armpad



Height adjustable armrest, one hand operation

# Frame



Standard frame



Neuro Frame

■ Standard	Life i			
### Ant-Hip tubes, swing-away ka plug in			Clanderd O Ne cost entire   Cost entire	Dries in 6
Liceoscope				Price in €
Libescope	1.110000004			
UB000002			The second area, s	leels)
MANGERS & FOOTPLATES			1 0 71	
HANGERS & FOOTPLATES			11 0 0	
	L11030044		And the plug in pair	
			HANGERS & FOOTPLATES	
LIBSS0012				
Month   Mont	L11050002	0		
L0050007				
				& 7")
LibsS0008	L11050005			
URBOSCO2	LII050006			
URBOSCO2			0	
Missoro	1.050000			
Hanger, composit, swing-away, pair			· ·	
Hanger, composit, swing-away, LH				
Hanger, aluminium, flip-up (0° - 90°), swing-away, Pair	211000000		Tranger, composit, swing away, Err	
Hanger, aluminium, flip-up (0° - 90°), swing-away, LH				olate)
Hanger, aluminium, flip-up (0" - 90"), swing-away, RH	LII050011			mm)
Amputee Support, left				
Mamputee support, left	LII050010		Hanger, aluminium, flip-up (0° - 90°), swing-away, RH	
Mamputee support, left			Amputee Support Pad	
Lineson   Amputee support, right   Amputee support, pair   Footplate   Footplate   Footplate   Footplate   Footboard, divided, composit, angle-adjustable, flip-up (sideways), heel loop, black   (1)   Lineson   Footboard, divided, aluminum, angle-adjustable, flip-up (sideways), heel loop, black   (7)   Lineson   Footboard, divided, aluminum, angle-adjustable, flip-up (sideways), heel loop, black   (2)   Lineson   Footboard, platform, aluminum, angle-adjustable, flip-up (sideways), heel loop, black   (2)   Lineson   Footboard, platform, aluminum, angle-adjustable, flip-up (sideways), heel loop, black   (2)   Lineson	LII050014			
Footplate  Li0550220	LII050013			
### Prothoard, divided, composit, angle-adjustable, flip-up (sideways), heel loop, black (1)   #### Contboard, divided, aluminum, angle-adjustable, flip-up (sideways), heel loop, black (**mm**LLL.360 mm**)   ##################################	LII050012			
### Prothoard, divided, composit, angle-adjustable, flip-up (sideways), heel loop, black (1)   #### Contboard, divided, aluminum, angle-adjustable, flip-up (sideways), heel loop, black (**mm**LLL.360 mm**)   ##################################			Factulate	
Footboard, divided, aluminum, angle-adjustable, flip-up (sideways), heel loop, black (from LLL 360 mm)	1.11050020	_	•	(1)
LI080023				<del>''</del>
LIOWER LEG LENGTH (LLL) - LLL has to be 25 mm lower than front seat height; all measurements in mm    340   350   360   370   380   390     400   410   420   430   440   450     460   470   480   490   500				
0 340			, p	<del>\-/ </del>
0 340			LOWER LEG LENGTH (LLL) - LLL has to be 25 mm lower than front seat height; all measure	ments in mm
Castor   Castor   Solid (soft), rim: composite, black   (compare with your choice on the first page)		_		
FORK    Compare with your choice on the first page				
FORK    Compare with your choice on the first page				
Liloso029			400 0 470 0 460 0 490 0 500	
Liloso029				
Lilo80042  Colour Cast. Fork Silver  Lilo80043  Colour Cast. Fork Orange  Lilo80101  Hemi kit  (Not in combination with 7" castors; standard frame only)  CASTOR  (compare with your choice on the first page)  Lilo80301  Castor, solid (hard), rim: composite, black  (only for 5" & 6" castors)  Lilo80302  Castor, solid (soft), rim: composite, black  (only for 6" & 7" castors)  Lilo80305  Castor, pneumatic, rim: composite, black  (only for 6" & 7" castors)  Lilo70000  Whithout wheels  Lilo70000  Rear wheel, Universal, 36 spokes (silver), cross-wise spokes  Lilo70000  Rear wheel, Lightweight, 24 spokes (silver), straight spokes  (only 24")  Lilo70000  Rear wheel, Lightweight, 24 spokes (silver), straight spokes  (max. user weight: 125 kg)  Lilo70000  Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes  Cone-hand operation  Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation  (3)  Lilo70401  Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation  (3)  Cone-hand operation  (3)  Lilo70402  Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation  (3)  Colour Cast. Fork Orange  (Not in combination with ELR				page)
CASTOR  (compare with your choice on the first page)  Lilo80301	L11080029	•		
CASTOR  (compare with your choice on the first page)  Lilo80301				
LII080301 O Castor, solid (hard), rim: composite, black LII080302 O Castor, solid (soft), rim: composite, black LII080305 O Castor, pneumatic, rim: composite, black LII080305 O Castor, pneumatic, rim: composite, black  REAR WHEELS (compare with your choice on the first page; choose only one wheel type)  LII070000 O Whithout wheels LII070001 O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes LII070002 O Rear wheel, Design, 36 spokes (silver), straight spokes LII070003 O Rear wheel, Lightweight, 24 spokes (silver), straight spokes LII070008 D Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes  One-hand operation  LII070401 Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wh	LII080101		Hemi kit (Not in combination with 7" castors; standard frame	only)
LII080301 O Castor, solid (hard), rim: composite, black LII080302 O Castor, solid (soft), rim: composite, black LII080305 O Castor, pneumatic, rim: composite, black LII080305 O Castor, pneumatic, rim: composite, black  REAR WHEELS (compare with your choice on the first page; choose only one wheel type)  LII070000 O Whithout wheels LII070001 O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes LII070002 O Rear wheel, Design, 36 spokes (silver), straight spokes LII070003 O Rear wheel, Lightweight, 24 spokes (silver), straight spokes LII070008 D Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes  One-hand operation  LII070401 Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation Rear wh			OACTOR	
Lilio80302	1.110000004			page)
Castor, pneumatic, rim: composite, black   Compare with your choice on the first page; choose only one wheel type				- ( )
REAR WHEELS (compare with your choice on the first page; choose only one wheel type)  LII070000  O Whithout wheels  LII070001  O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes  LII070002  O Rear wheel, Design, 36 spokes (silver), straight spokes  LII070003  O Rear wheel, Lightweight, 24 spokes (silver), straight spokes  LII070008				
LII070000  O Whithout wheels LII070001  O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes LII070002  O Rear wheel, Design, 36 spokes (silver), straight spokes	LIIU0U3U3		Castor, prieumatic, nin. composite, black	siors)
LII070000  O Whithout wheels LII070001  O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes LII070002  O Rear wheel, Design, 36 spokes (silver), straight spokes			DEAD WHEELS (compare with your choice on the first page; choose only one wheel	type)
LII070001 O Rear wheel, Universal, 36 spokes (silver), cross-wise spokes  LII070002 O Rear wheel, Design, 36 spokes (silver), straight spokes  LII070003 O Rear wheel, Lightweight, 24 spokes (silver), straight spokes  LII070008 Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes  One-hand operation  LII070401 Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation  LII070402 Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation  (3)  (1) pair; from LLL 340 mm; only from SW 360 mm  For more information  www.SunriseMedical.eu	L 11070000	0		iype)
LII070002 O Rear wheel, Design, 36 spokes (silver), straight spokes (only 24")  LII070003 O Rear wheel, Lightweight, 24 spokes (silver), straight spokes (max. user weight: 125 kg)  LII070008 Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes (only with 0° camber)  One-hand operation  LII070401 Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation (3)  LII070402 Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation (3)  (1) pair; from LLL 340 mm; only from SW 360 mm  (2) from LLL 360 mm; not in combination with ELR				
LII070003 O Rear wheel, Lightweight, 24 spokes (silver), straight spokes (max. user weight: 125 kg) LII070008 Rear wheel, drum brakes, 36 spokes (silver), cross-wise spokes (only with 0° camber)  One-hand operation LII070401 Rear wheel, one-hand operation, 36 spokes, cross-spoked, left actuation LII070402 Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation (3) LII070402 Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation (3)  (1) pair; from LLL 340 mm; only from SW 360 mm (2) from LLL 360 mm; not in combination with ELR				/ 24")
LII070008				
One-hand operation  LII070401			7 0 0 7 1 ( 7 0 1	
LII070401			, , , , , , , , , , , , , , , , , , , ,	
LII070402 Rear wheel, one-hand operation, 36 spokes, cross-spoked, right actuation  (1) pair; from LLL 340 mm; only from SW 360 mm (2) from LLL 360 mm; not in combination with ELR  (3)  For more information www.SunriseMedical.eu	L HOMO (T)		•	(0)
(1) pair; from LLL 340 mm; only from SW 360 mm (2) from LLL 360 mm; not in combination with ELR  For more information  www.SunriseMedical.eu				
(2) from LLL 360 mm; not in combination with ELR www.SunriseMedical.eu	L11070402	П	real wheel, one-hand operation, 36 spokes, cross-spoked, right actuation	(3)
(2) from LLL 360 mm; not in combination with ELR www.SunriseMedical.eu	(1)	nair	from LLL 340 mm; only from SW 360 mm	For more information
	(3)			

### **HANGERS & FOOTPLATES**



Aluminum hanger, 90°



Composite hanger



Elevating legrest



Amputee Support Pad



Divided angle adjustable footplates composite



Divided, angle adj depth adjustable, aluminum



Platform, angle and depth adjustable, flip up, aluminum

69

#### Fork



Fork Aluminium, black, orange & silver

#### **REAR WHEELS & TYRES**



Universal cross spoked



Design wheel



Lightweight wheel



Right Run Tyre



Solid Tyre



Marathon Plus Evolution



Supergrip



Max Grepp



Ellipse 3R Handrim

© Sunrise Medical 2024

Life i			
	•	= Standard O = No cost option □ = Cost option	Price in €
		TYRES (choose only one tyre	type)
LII070101	0	Tyre, pneumatic, fine profile, Schwalbe Right Run	
LII070102	0	Tyre, puncture proof, tread	
LII070104		Tyre, pneumatic, puncture proof, tread, Schwalbe Marathon Plus Evolution	
		HANDRIM	
LII070204	0	Handrims, stainless steel, silver	T I
LII070202	0	Handrims, atamiess steer, silver	
LII070201	0	Handrims, aluminium, powder-coated, clear	
L11070207		Handrims, Supergrip ® (22" only with universal and drum brake wh	neels)
L11070208		Handrims, Maxgrepp ® (only handrim miounting	wide)
LII070212		Handrims, Ellipse 3R, black (ergonomic handrims with rubber-strip, 24" and 25"	only)
		Handrim mount	
L11070307		Handrim mount, super narrow = 7 mm (only with stainless s	steel)
LII070317	•	Handrim mount, narrow = 17 mm (12,5 mm with lightweight wheels, not with Maxgr	ırерр)
LII070327	0	Handrim mount, wide = 27 mm (not with lightweight wheel and alu han	ndrim)
		Handrim Cover	
L11070250		Handrim cover, silicon	
	_		
1 11070000		WHEEL CAMBER (choose only one option; Armrests only with	ith 0°)
LII070600 LII070603	0	Wheel camber 0° Wheel camber 3° (not with drumbrake wheel, one arm of the camber 3°)	dri (a)
_11070003		Wheel camper 3	arive)
		SPOKE GUARDS	
LII070831		Transparent	
		LII070813 □ Glaktica	
LII070823			
LII070816		Happy Lions	<del></del>
LII070819 LII070820		Monkeys LII070821 □ Pirates LII070811 □ Feather  Oriental	<del>                                     </del>
LII070820 LII070829		Superhero LII070814   Graffiti   LII070806   Chrome	
LII070817		Hot Wheels LII070802 □ Basketball LII070803 □ Basketball 2	
L11070822		Pool LII070812	
L11070827		Silk	
L11070830		Tiger	
		WHEEL LOCKS (choose only one op	enting)
LII060002	-	WHEEL LOCKS (choose only one on Knee lever wheel lock	ption)
LII060010		Extension for knee lever wheel lock, slip-on, swing-away	
		· · · · · · · · · · · · · · · · · · ·	
LII060015		Push to lock, one-arm way  Push to lock, one-arm way, left actuation	<del></del>
LII060016		Push to lock, one-arm way, right actuation	
		ACCESSORIES	
L11090000		Tool kit	
L11090025		Air pump High pressure pump	
L11090024 L11090030		Back pack	
L11090030 L11090026		Mobile phone pocket	
			For more information
			www.SunriseMedical.eu
			© Sunrise Medical 2024

# WHEEL LOCKS







Extension for knee lever wheel lock, slipon and swing away

# **ACCESSORIES**



Tool kit



Back pack



High pressure pump



Air pump



Mobile phone pocket

# TRAYS



Half side tray

Life i		
● = Standard O = No cost optic	n □ = Cost option	Price in €
TRAYS		
Swing away tray		
LII090012 ☐ Swing away tray, left side mounted	(only with armrest height adjustable, fr	om SW 400 mm)
LII090013 ☐ Swing away tray, right side mounted	(only with armrest height adjustable, fr	om SW 400 mm)
Half side tray		
LII090045 ☐ Half side tray, left side mounted	(only with armrest h	eight adjustable)
LII090046 ☐ Half side tray, right side mounted	(only with armrest h	eight adjustable)
		•
LII090011 □ Slide on tray	(SW 380	) mm to 480 mm)
COLOURS (1) Please consult of	ur colour catalogue to review your colour choice	
F	F	
Frame	Frame	
02 Brilliant Silver	27 Graphitemetallic	
03 Silver Matt □	29 Black	
06 Sun Yellow	31 Matt Black	
14 Blue O	32 Signal White	
15 Brilliant Marine O	33 Pink O	
16 Matt Marine □	34 Dark Chocolate Metallic □	
19 Brilliant Purple O	35 Skyblue □	
21 Red Ruby O	36 Cyan-Metallic □	
22 Brilliant Red □	37 Marsred (Orange) □	
23 Matt Red □	40 Kiwi □	
24 Tutti Frutti Orange O	41 Flamingo-Glitter □	
	42 Matt-Anthracite O	
	46 Mamba Green (new) □	
(1) Handrim: only with handrim colour powder coated; I	dub/rim: only for universal wheel 22", 24"	
STICKER COLOURS		
LII100550 O Sticker colour - black		-
LII100551 O Sticker colour - silver		-
Comments for special build - please apply for a	a quoto: land time conditions my change	
Comments for special build - please apply for a	i quote; lead time conditions my change.	
		built <mark>4</mark> me
Quickie Life i - Basic Price		€
Option price		€
Packaging and transport		€
Exclusive VAT		€
VAT.		
Total Price		€
Sunrise Medical Customer service		For more information
Address: Ul. Walczaka 114a,66 400, Gorsaw, Gorzóv	w Wikn Polen	visit our webpage
Tel. +48 95 737 25 14	E-mail: cs.pl@sunrise-medical.pl	www.SunriseMedical.eu
	Website: www.sunrisemedical.eu	© Sunrise Medical 2024