Deliver to: Name: Street: Town: Postal code: Town: Postal code: Street: Town: Postal code: E-Mail: Tel: Fax: Tel:		MEDICAL. VA	lid until: 11.25			ELDRIVE
Street:	eliver to:					
Postal code: Post						
Mail: # Fax: # Fax: # Fax: # Fax: # # # # # # # # # # # # # # # # # # #		Dootel ander			Dantal	
TECHNICAL DATA WheelDrive // Writer in Catal weight including battery (one wheel) 11.5 kg Weel diameter 12.7 mm (br and weight including battery (one wheel) 12.4 wheel diameter 12.7 mm (br and weight including battery with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WHEELDRIVE SET WHEELDRIVE SET WHEELDRIVE SET 1019498		Postal code.		·	Postai	code.
Marked for:		Fav:			Fay:	
TECHNICAL DATA WheelDrive // WHEELCHAIR POWER ASSIST Max. load capacity Total width compared to manual wheels (set) 43 mm Weight of batteries (set) 3.6 kg Total weight including battery (one wheel) 11.5 kg Wheel diameter 24* Wheel Drive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019498 WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (choose avide diameter 12.7 mm (25-75mm), (only HeliX) 9011415 Mounting set, quick-release axide diameter 12.7 mm (25-75mm), (only HeliX) 9011416 Mounting set, quick-release axide diameter 12.7 mm (25-75mm), (only HeliX) 9011417 Mounting set, quick-release axide diameter 12.7 mm, short (for axie plate 37 mm) 9011419 Spoke quards 24*, set 1019491 Spoke quards 24*, set 1019491 Spoke quards 24*, set 1019492 Spoke quards 24*, set 1019491 Spoke quards 24*, set		i ax.			ı ax.	
Sunrise order no:				Marked for:		
Customer service fax number: + 31 (0) 492593888 Max. user weight: 130 kg TECHNICAL DATA				Sunrise order no:		
Max. user weight: 130 kg		Order □ Calculation □ Built 4 me				Cost option
TECHNICAL DATA WheelDrive // WHEELCHAIR POWER ASSIST Max. Ioad capacity Total width compared to manual wheels (set) 43 mm Weight of batteries (set) Total weight including battery (one wheel) 11.5 kg Total weight including battery (one wheel) 9.7 kg Wheel diameter Wheel diameter WHEELDRIVE SET 1019498 WhoelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (choose applicable mounting set) Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 Mounting set, quick-release axle diameter 12.7 mm (25-75mm) Mounting set, quick-release axle diameter 12.7 mm, (56-55mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Spoke guards 24", set 1019491 Additional batteries 3.8 Ah, set				•		+ 31 (0) 492593888
TECHNICAL DATA WheelDrive // WHEELCHAIR POWER ASSIST Max. load capacity 130 kg Total width compared to manual wheels (set) 43 mm Weight of batteries (set) 3.6 kg Total weight including battery (one wheel) 11.5 kg Total weight including battery (one wheel) 11.5 kg Wheel diameter 24* Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B Price in € WHEELDRIVE SET 1019498 WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019499 WheelDrive with 24* Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) Mounting set, quick-release axle diameter 12.7 mm (25-55mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES Spoke quards 24*, set 1019491 Spoke quards 24*, set 1019491 Additional batteries 3.8 Ah, set						. ,
WheelDrive // WHEELCHAIR POWER ASSIST Max. load capacity				wax. user weign	it:	130 Kg
Total width compared to manual wheels (set) 43 mm Weight of batteries (set) 3.6 kg Total weight including battery (one wheel) 11.5 kg Total weight including battery (one wheel) 9.7 kg Wheel diameter 24" Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B **Price in €** **WHEELDRIVE SET** 1019498 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left **WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left **WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left **WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left **WheelDrive mounting** 9011415 ○ Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9911414 ○ Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9911415 ○ Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9911416 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) **ACCESSORIES** 1019491 □ Spoke guards 24", set 1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set						
Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter 124° Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B **Price in € **WHEELDRIVE SET* 1019498 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019499 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left **WheelDrive mounting (Choose applicable mounting set) 9011415 ○ Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 ○ Mounting set, quick-release axle diameter 12.7 mm (55-65mm) 9011415 ○ Mounting set, quick-release axle diameter 12.7 mm (55-65mm) 9011410 ○ Mounting set, quick-release axle diameter 12.7 mm (55-65mm) 9011411 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011418 ○ Spoke guards 24", set 1018562 ○ Push rim cover 24", silicone, set (for assist rim) 1016015 ○ Additional batteries 3.8 Ah, set				Many are and forward (a soint six)	40 1 #:	¬
Total weight including battery (one wheel) Total weight excluding battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B Price in € WHEELDRIVE SET 1019498 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019499 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) 9011415 ○ Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 ○ Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 □ Spoke guards 24", set 1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set		Max. load capacity	130 kg			
Total weight excluding battery (one wheel) 9.7 kg Wheel diameter 24" Max. kerb climbing, driving backwards 50 mm Charging time (full charge) Approx. 2 hours Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B Price in € WHEELDRIVE SET 1019498 WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019499 WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) 9011415 Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Spoke guards 24", set 1018562 Push rim cover 24", silicone, set (for assist rim) 1016015 Additional batteries 3.8 Ah, set		Max. load capacity Total width compared to manual wheels (set)	130 kg 43 mm	Max. speed forward (drive rim)	6 km/h	
Intended use and environment: For people with limited mobility; self-propelling; indoor and outdoor use. Wheelchair type class B Price in €		Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set)	130 kg 43 mm 3.6 kg	Max. speed forward (drive rim) Max. range (assist rim)	6 km/h 20 km	
WHEELDRIVE SET 1019498 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right 1019499 ○ WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) 9011415 ○ Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 ○ Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) 9012380 ○ Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 ○ Mounting set, quick-release axle diameter 12 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 ○ ACCESSORIES 1019491 □ Spoke guards 24", set 1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set		Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel)	130 kg 43 mm 3.6 kg 11.5 kg	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim)	6 km/h 20 km 12 km	
WHEELDRIVE SET 1019498 WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - right WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) 9011415 Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) 9012380 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 Mounting set, quick-release axle diameter 12 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Spoke guards 24", set 1018562 Push rim cover 24", silicone, set (for assist rim) 1016015 Additional batteries 3.8 Ah, set		Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel)	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards	6 km/h 20 km 12 km 50 mm	
1019498		Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24"	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge)	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in £
1019499 WheelDrive with 24" Marathon Plus Evolution tyre, pneumatic, puncture proof - left WheelDrive mounting (Choose applicable mounting set) 9011415 Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) Mounting set, quick-release axle diameter 12.7 mm (25-65mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm (25-65mm) Mounting set, quick-release axle diameter 12.7		Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24"	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge)	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
9011415 O Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 O Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) 9012380 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 D Spoke guards 24", set 1018562 Push rim cover 24", silicone, set (for assist rim) Additional batteries 3.8 Ah, set	1019498	Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim	130 kg	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair type	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
9011415 O Mounting set, quick-release axle diameter 12.7 mm (25-75mm), (only HeliX) 9011414 O Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) 9012380 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Despries Spoke guards 24", set 1018562 Push rim cover 24", silicone, set (for assist rim) 1016015 Additional batteries 3.8 Ah, set		Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evol	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" anited mobility; self-propution tyre, pneumati	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typeling, puncture proof - right	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
9011414 O Mounting set, quick-release axle diameter 12 mm (for axle plate 25 - 75 mm) 9012380 Mounting set, quick-release axle diameter 12.7 mm (25-65mm) 9011416 Mounting set, quick-release axle diameter 12 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) **ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) **ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) **ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) **ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES** 1019491 Mounting set, quick-re		Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" anited mobility; self-propution tyre, pneumatiution tyre, pneumati	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typeling, puncture proof - right	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
9011416 Mounting set, quick-release axle diameter 12 mm, short (for axle plate 37 mm) 9011417 Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Spoke guards 24", set 1018562 Push rim cover 24", silicone, set (for assist rim) 1016015 Additional batteries 3.8 Ah, set	1019499	Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose appli	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" 24" ution tyre, pneumation tyre, pneumation tyre, pneumaticable mounting set)	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
9011417 O Mounting set, quick-release axle diameter 12.7 mm, short (for axle plate 37 mm) ACCESSORIES 1019491 Spoke guards 24", set Spoke guards 24", set Push rim cover 24", silicone, set (for assist rim) 1016015 Additional batteries 3.8 Ah, set	1019499 9011415	Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameter	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" ution tyre, pneumatiution	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
ACCESSORIES 1019491 □ Spoke guards 24", set 1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set	9011415 9012380	Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameted Mounting set, quick-release axle diameted Mounting set, quick-release axle diameted	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" ution tyre, pneumatiution	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; puncture proof - right ic, puncture proof - left m), (only HeliX) plate 25 - 75 mm) m)	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
1019491 □ Spoke guards 24", set 1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set	9011415 9012380 9011416	Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameter	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" whited mobility; self-proputation tyre, pneumaticution tyre, pneumaticutio	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
1018562 □ Push rim cover 24", silicone, set (for assist rim) 1016015 □ Additional batteries 3.8 Ah, set	9011415 90112380 9011416	Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameted	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" whited mobility; self-proputation tyre, pneumaticution tyre, pneumaticutio	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
1016015 Additional batteries 3.8 Ah, set	9011415 9011416 9011416 9011416 9011417	Max. Ioad capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evol WheelDrive with 24" Marathon Plus Evol WheelDrive mounting (Choose appl Mounting set, quick-release axle diamete	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" whited mobility; self-proputation tyre, pneumaticution tyre, pneumaticutio	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
	9011415 9011416 9012380 9011416 9011417	Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameter ACCESSORIES Spoke guards 24", set	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" hited mobility; self-proputation tyre, pneumaticution	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €
	9011415 9011416 9012380 9011416 9011417 1019491 1018562	Max. load capacity Total width compared to manual wheels (set) Weight of batteries (set) Total weight including battery (one wheel) Total weight excluding battery (one wheel) Wheel diameter Intended use and environment: For people with lim WHEELDRIVE SET WheelDrive with 24" Marathon Plus Evolution WheelDrive with 24" Marathon Plus Evolution WheelDrive mounting (Choose application) Mounting set, quick-release axle diameter Spoke guards 24", set Push rim cover 24", silicone, set (for assi	130 kg 43 mm 3.6 kg 11.5 kg 9.7 kg 24" hited mobility; self-proputation tyre, pneumaticution	Max. speed forward (drive rim) Max. range (assist rim) Max. range (drive rim) Max. kerb climbing, driving backwards Charging time (full charge) pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use. pelling; indoor and outdoor use. Wheelchair typelling; indoor and outdoor use.	6 km/h 20 km 12 km 50 mm Approx. 2 hours	Price in €

Wheeldrive Option price Packaging and transport Exclusive VAT VAT. Total Price Sunrise Medical Customer service F-mail: customerservice@sunrisemedical.pl

Tel. +31(0)492 593 888 E-mail: customerservice@sunrisemedical.nl Fax. +31 (0)492 546 497 Website: sunrisemedical.eu

